

Barcode Label Printer DT & TT



EC-Q8-PLUS Specifications

Printing Method	Direct Thermal & Thermal Transfer
Printing Resolution	203 dpi (8 dots/mm)
Max Printing Speed	4 ips (101.6 mm/s)
Max Printing Width	4.25" (108 mm)
Max Printing Length	157"(4000 mm)
Memory	32-bit ARM Processor, 2 MB FLASH ROM, 8 MB SDRAM
Media	Roll-feed, die-cut, continuous, tags, tickets in plain paper or thermal paper Width: 110 mm max., 25 mm min. Supply roll: OD 5" (127 mm) max., ID 1" (25.4 mm) min. Thickness: 0.003"~0.006" (0.08~0.15 mm), including liner
Ribbon	Wax, Wax/Resin, Resin Ribbon roll: OD 1.5" (38 mm) max., ID 0.5" (12.7 mm) core Max width: 110 mm; Max length: 110 M. Ink side: Out
Fonts	Five built-in ASCII fonts; Optional multiple language fonts
Bar Code Types	1D Barcode: Code 39, Code 93, Code 128/subset A,B,C, Codabar, Interleave 2 of 5, UPC A/E 2 and 5 add-on, EAN-13/8/128, UCC-128 2D Barcode: MaxiCode, PDF417, Data Matrix, QR
Media sensor	Reflective (multiple mounting positions)
Interfaces	RS-232 serial, USB
Power rating	24 VDC Power adapter
Weight	4.62 lbs (2.1 kgs)
Dimensions	W 8.27" x D 10.04" x H 5.9" (W 210 x D 255 x H 150 mm)
Operation Environment	Temperature: 32° F ~ +104° F (0° C ~ 40° C) Relative humidity: 5% - 85% non condensing
Storage Environment	Temperature: -40° F ~ +140° F (-40° C ~ 60° C) Relative humidity: 5% - 85% non condensing
Optional Items	Guillotine Cutter, Peeler Kit, External Rewinder