

Touch Screen Monitor



EC-TS-1210

Features

- LIYITEC/Wan da five-wire resistive technology
- Drip-proof enclosure, touchscreen sealed
- Touch can be activated with gloved hands
- Multiple mounting options including VESA
- Built in speakers (optional)
- On screen display controls on the side

Specifications

Display type	12"LCD Touch monitor
Color	Black
Optional items	ISO Track 1/2/3 Magnetic Stripe Reader & VFD
Pixel	0.3075(W)×0.3075(H) mm
Display area	246.0(W)×184.5(H) mm
Contrast	450:1
View Angle	Horizon: 140; Vertical: 110
Tilting Angle	0-90 degrees
LCD Panel size	12 inch TFT LCD
Line frequency	30KHZ-61KHZ
Field frequency	50HZ-75HZ
Display color	16.2M
Resolution	XGA 800*600@60Hz
Brightness	330cd/m ²
Response	6ms
Touch screen	4 wire Resistive touchscreen
Touch interface	USB B type
Rear I/O ports	Analog: 15-pin-D-SUB, USB touch input, DC 12V input, Audio: line in (optional)
Side I/O port	USB A type port
Power Consumption	25W(max)
EMI/ Product Safety	TUV,CE,VCCI,FCC
Operating Humidity	20%~80%
Operating Temperature	0 °C to 40 °C
Storage Humidity	20%~80%
Storage Temperature	-20 °C to 60 °C
Packing dimension	360*390*170mm
Package: carton box with Foam pa	NW: 3.7KG GW: 5.5KG
Power adaptor	100-250V/50-60HZ AC power input ,DC 12V/3A output
other function cable	VGA cable, USB B type cable for touch ,Audio cable (audio function optional)