

DR-6030C



A3

Capture Perfect

*Web Download Only

Capture OnTouch

- The same fast scanning speed for color, grayscale, and B&W
- 60 ppm simplex and 120 ipm duplex (A4/LTR, 200 dpi)
- High speed and exceptional color accuracy with advanced 3-line CIS sensor
- Skew Detection and Ultrasonic Double Feed Detection for smooth feeding of a wide range of documents
- Advanced functions including Custom Color Dropout and Text Enhancement modes
- Bundled with CapturePerfect and VRS



Scanning speed			Document size	
A4/LTR, Portrait, 200dpi:			Plain paper	A3/LGL Width: 53 – 300 mm, Length: 70 – 432 mm
	Simplex	Duplex	Long document	✓ Up to 3,000 mm
Black and white	60 ppm	120 ipm	Postcard	✓ Width: 89-108 mm, Length: 127 – 152 mm
Grayscale	60 ppm	120 ipm	Business card	✓ Width: 53 – 55 mm, Length: 70 – 91 mm (Vertical feeding only)
Color	60 ppm	120 ipm	Card (ISO/IEC compliant)	✓ 54 x 86 mm (Straight path, non-separate feeding only)
A4, Landscape, 200dpi:			Feeding Capacity	
	Simplex	Duplex	100 sheets	
Black and white	80 ppm	160 ipm		
Grayscale	80 ppm	160 ipm		
Color	80 ppm	160 ipm		

*Actual scanning speed may vary depending on your system configuration and PC

Type		Desktop sheetfed scanner		Scanning side		Simplex / Duplex	
Scanning element		3-line CIS		Interface		Hi-speed USB 2.0	
Light source		LED (red, green and blue)		Bundled software		CapturePerfect, VRS	
Feeding method		Automatic or manual		Power supply		AC 220 – 240 V	
Document thickness	Plain paper	U-turn path, feeding with separate mode		Power consumption		Scanning: 38.1 W, Sleep Mode: 2.5 W	
		Weight: 52 – 128 g/m ²				Power Turned OFF: 0.4 W	
		Thickness: 0.06 – 0.15 mm					
		Straight path, feeding with separate mode					
		Weight: 42 – 157 g/m ²					
		Thickness: 0.05 – 0.2 mm					
		U-turn path, feeding with bypass mode					
		Weight: 52 – 128 g/m ²					
		Thickness: 0.06 – 0.2 mm					
		Straight path, feeding with bypass mode					
		Weight: 42 – 546 g/m ²					
		Thickness: 0.05 – 0.66 mm					
	Card (ISO/IEC compliant)	0.76 mm or less					
				Operating environment		Temperature	
						10 – 32.5°C	
						Humidity	
						20 – 80% RH	
						Dimensions (width × depth × height)	
						Trays closed: 398.4 × 312 × 191.4 mm	
						Trays open: 398.4 × 668 × 194 mm	
						Weight	
						Approx. 10.2 kg	
				Options/consumables		Barcode Module, Exchange Roller Kit, Flatbed Scanner Unit 102	