

# DR-C225 II/C225W II



A4

Capture OnTouch

**WiFi**  
 CERTIFIED  
 (DR-C225W II only)

**Wi-Fi PROTECTED  
 SETUP**  
 (DR-C225W II only)

- Switchable straight/U-turn path allows slim, upright design
- Natural and intuitive face-up feeding
- Fast scanning at 25 ppm / 50 ipm, both color and B&W, single-pass double-sided
- Superb image quality at up to 600 dpi
- Reliable feeding of a wide range of documents, including embossed plastic cards
- Double feed detection ensures smooth feeding
- Batch scanning features include Full Auto Mode, Skip Blank Page, Text Orientation Recognition, and more
- Bundled software includes CaptureOnTouch
- Windows & Mac compatibility
- Built-in wireless unit allows cableless scanning and connectivity to smart devices (DR-C225W II)
- Easy setup and preparation for connections using WPS (DR-C225W II)



Scanning speed		Document size	
A4/LTR, Portrait, 200dpi:		Plain paper	A4/LTR Width: 51 – 216 mm, Length: 54 – 356 mm
	<div style="display: flex; justify-content: space-around;"> <span>Simplex</span> <span>Duplex</span> </div>	Long document	✓ Up to 3,000 mm
Black and white	25 ppm      50 ipm	Postcard	✓ Width: 89 – 108 mm, Length: 127 – 152 mm
Grayscale	25 ppm      50 ipm	Business card	✓ Width: 51 – 54 mm or larger (Vertical feeding only)
Color	25 ppm      50 ipm	Card (ISO/IEC compliant)	✓ 54 x 86 mm (Straight path and horizontal feeding only. Embossed cards can be scanned)
*Actual scanning speed may vary depending on your system configuration and PC			
		Feeding Capacity	
		30 sheets	

Type	Desktop sheetfed scanner		Power supply	AC100 – 240 V
Scanning element	CIS		Power consumption	DR-C225 II: Scanning: 12.8 W, Sleep mode: 1.8 W, Power Turned OFF: 0.5 W
Light source	LED (red, green and blue)			DR-C225W II: Scanning: maximum 15.6 W, Sleep mode: maximum 4.4 W, Power Turned OFF: maximum 0.5 W
Feeding method	Automatic		Operating environment	Temperature 10 – 32.5°C
Document thickness	Plain paper	U-turn path Weight: 52 – 128 g/m <sup>2</sup> Thickness: 0.06 – 0.15 mm	Humidity	20 – 80% RH
		Straight path Weight: 40 – 209 g/m <sup>2</sup> Thickness: 0.05 – 0.25 mm		Dimensions (width x depth x height)
	PostCard Weight: 128 – 300 g/m <sup>2</sup> Thickness: 0.15 – 0.4 mm <i>*PostCard can be scanned with straight path only.</i>	Feed tray closed: 300 x 156 x 220 mm		
	Business card Weight: 300 g/m <sup>2</sup> or less Thickness: 0.35 mm	Weight	Feed tray open: 300 x 235 x 336 mm	
Card (ISO/IEC compliant) 0.76 mm or less	Interface	DR-C225 II: Approx. 2.7 kg DR-C225W II: Approx. 2.8 kg		
Scanning side	Simplex / Duplex		Options/consumables	Flatbed Scanner Unit 102 (The DR-C225W II is compatible only with a USB connection), Exchange Roller Kit
Bundled software	Windows: ISIS/TWAIN driver, CaptureOnTouch, Scanner Wireless Connection Setup Tool <sup>*1</sup> , Network Monitor <sup>*1</sup>  Mac: TWAIN driver, CaptureOnTouch, Scanner Wireless Connection Setup Tool <sup>*1</sup> , Network Monitor <sup>*1</sup>  *1 DR-C225W Only.			