

DR-F120



ADF Flatbed



Capture OnTouch

- 2-way design (ADF, flatbed) will reliably handle a variety of documents
- Reliable paper transport ensures smooth feeding
- Fast scanning of A4/LTR at 10 ppm / 18 ipm (color), 20 ppm / 36 ipm (grayscale, B&W), single-pass double-sided
- The flatbed supports LGL documents
- Batch scanning features include Skip Blank Page, Text Orientation Recognition, and more
- "CaptureOnTouch" ready
- Supports 1200 / 2400 dpi output resolution



Scanning speed		Document size	
A4/LTR, Portrait, 200dpi:		Plain paper	A4/LTR ADF -- Width: 51 – 216 mm, Length: 89 – 356 mm Flatbed -- Width: 216 mm, Length: 356 mm
	Simplex	Long document	✓ Up to 1,000 mm
Black and white	20 ppm	Postcard	✓ Width: 89 – 108 mm, Length: 127 – 152.4 mm (with flatbed)
Grayscale	20 ppm	Business card	✓ Width: 51-55 mm, Length: 85 – 91 mm
Color	10 ppm	Card (ISO/IEC compliant)	✓ Width: 86 mm, Length: 54 mm (with flatbed, and embossed card can be scanned)
<small>* When scanning documents using ADF. Actual scanning speed may vary depending on your system configuration and PC.</small>		Feeding Capacity	
		50 sheets (ADF)	

Type	Desktop ADF (Automatic Document Feeder) / flatbed scanner		Scanning side	Simplex / Duplex
Scanning element	CIS		Interface	Hi-speed USB 2.0
Light source	LED (red, green and blue)		Bundled software	ISIS/TWAIN Driver, CaptureOnTouch
Feeding method	Automatic / flatbed		Power supply	AC100 – 240 V
Document thickness	Plain paper	Weight: 35 – 128 g/m ² Thickness: 0.05 – 0.15 mm	Power consumption	
	PostCard	Weight: 128 - 209.5g/m ² Thickness: 0.15 - 0.25 mm	Operating environment	Scanning: 33 W, Sleep mode: 3.7 W Power Turned OFF: less than 0.5 W
	Business card	Weight: 128 – 209.5 g/m ² Thickness: 0.15 – 0.25 mm	Temperature	10 – 32.5°C
	Card (ISO/IEC compliant)	0.76 mm or less	Humidity	20 – 80% RH
			Dimensions (width × depth × height)	Paper guide closed: 469 × 335 × 120 mm (Without ADF cable)
			Weight	Approx. 4.6 kg
			Options/consumables	Exchange Roller Kit