

# DR-G2140/G2110/G2090



A3

Capture OnTouch

- Fast, precise scanner with high-volume output capabilities
- Realizing both high-speed scanning and superior image quality by adopting new CIS and DR processor
- High durability of the paper feed roller and the transport roller for stable and reliable feeding
- Large-capacity feed tray with 3-step height adjustability
- Realizing effective binarization with the new "Active Threshold" function
- Support network scanning with wired LAN connection (DR-G2140, DR-G2110)
- User-friendly 5-Line LCD and key layout
- Assignable job key on an easy-to-use control panel



Scanning speed			Document size		
<b>DR-G2140 (Landscape, 200dpi):</b>			<b>Plain paper</b>		
	Simplex	Duplex	<b>A3/LGL</b> Width: 50 – 305 mm, Length: 70 – 432 mm		
	LTR/A4	LTR/A4			
Black and white	140/145 ppm	280/290 ipm	<b>Long document</b> ✓ DR-G2140, DR-G2110: Up to 5,588 mm DR-G2090: Up to 3,000 mm		
Grayscale	140/145 ppm	280/290 ipm			
Color	140/145 ppm	280/290 ipm	<b>Postcard</b> ✓ Width: 89-108 mm, Length: 127 – 152 mm		
<b>DR-G2110 (Landscape, 200dpi):</b>			<b>Business card</b> ✓ Width: 53 – 55 mm, Length: 85 – 91 mm (Vertical feeding only)		
	Simplex	Duplex			
	LTR/A4	LTR/A4			
Black and white	110/120 ppm	220/240 ipm	<b>Card (ISO/IEC compliant)</b> –		
Grayscale	110/120 ppm	220/240 ipm			
Color	110/120 ppm	220/240 ipm			
<b>DR-G2090 (Landscape, 200dpi):</b>			<b>Feeding Capacity</b>		
	Simplex	Duplex	<b>500 sheets (DR-G2140, DR-G2110)</b>		
	LTR/A4	LTR/A4	<b>300 sheets (DR-G2090)</b>		
Black and white	90/100 ppm	180/200 ipm			
Grayscale	90/100 ppm	180/200 ipm			
Color	90/100 ppm	180/200 ipm			
<b>DR-G2140 (Portrait, 200dpi):</b>					
	Simplex	Duplex			
	LTR/A4	LTR/A4			
Black and white	110/110 ppm	220/220 ipm			
Grayscale	110/110 ppm	220/220 ipm			
Color	110/110 ppm	220/220 ipm			
<b>DR-G2110 (Portrait, 200dpi):</b>					
	Simplex	Duplex			
	LTR/A4	LTR/A4			
Black and white	90/180 ppm	180/180 ipm			
Grayscale	90/180 ppm	180/180 ipm			
Color	90/180 ppm	180/180 ipm			
<b>DR-G2090 (Portrait, 200dpi):</b>					
	Simplex	Duplex			
	LTR/A4	LTR/A4			
Black and white	75/75 ppm	150/150 ipm			
Grayscale	75/75 ppm	150/150 ipm			
Color	75/75 ppm	150/150 ipm			

\*Actual scanning speed may vary depending on your system configuration and PC

<b>Type</b>		Desktop sheet-fed scanner	<b>Power supply</b>		AC 220 – 240 V
<b>Scanning element</b>		3-line CIS	<b>Power consumption</b>		Scanning: 66.5 W, Sleep mode: 3.5 W
<b>Light source</b>		LED (Red, Green)	<b>Operating environment</b>	<b>Temperature</b>	10 – 35°C
<b>Feeding method</b>		Automatic or manual sheet feeding		<b>Humidity</b>	20 – 80% RH
<b>Document thickness</b>	<b>Plain paper</b>	Continuous Feeding Weight: 20 – 209 g/m² Thickness: 0.04 – 0.25 mm	<b>Dimensions (width × depth × height)</b>		Feed trays closed: 480 × 569 × 315 mm
		Non-Separation Mode Weight: 20 – 255 g/m² Thickness: 0.04 – 0.30 mm	<b>Weight</b>		Approx. 25.0 kg
<b>Scanning side</b>		Simplex / Duplex	<b>Options/consumables</b>		Flatbed Scanner Unit 102, Imprinter Unit, Carrier sheet, Exchange roller kit, Separation Pads, Ink Cartridge, Cleaning Sheet
<b>Interface</b>		USB3.1 Gen1, 10Base-T/100Base-T/100Base-Tx/1000Base-T (DR-G2140, DR-G2110)			
<b>Bundled software</b>		CaptureOnTouch, VRS			