

DR-M160II



A4

Capture Perfect

Capture OnTouch

- Reliably scans variety of documents from thinnest of document sheets to multi-sheet forms
- ADF holds up to 60 sheets
- Fast scanning at 60 ppm / 120 ipm, both color and B&W, single-pass double-sided
- Ultrasonic double feed detection ensures smooth feeding
- Batch scanning features include Full Auto Mode, Skip Blank Page and Auto Page Size Detection
- Bundled software includes CaptureOnTouch, CapturePerfect, eCopy PDF Pro Office and VRS
- Windows & Mac compatibility
- The ADF (Automatic Document Feeder) can hold up to 75 sheets with certain condition of the paper size / thickness



Scanning speed			Document size	
A4/LTR, Portrait, 200dpi:			Plain paper	A4/LTR Width: 54 – 216 mm, Length: 50.8 – 356 mm
Black and white Grayscale Color	Simplex	Duplex	Long document	✓ Up to 3,000 mm
	60 ppm	120 ipm	Postcard	✓ Width: 89 – 108 mm, Length: 127 – 152 mm
	60 ppm	120 ipm	Business card	✓ Width: 51 – 55 mm, Length: 85-91 mm (Vertical feeding only)
*Actual scanning speed may vary depending on your system configuration and PC			Card (ISO/IEC compliant)	✓ 54 x 86 mm (Embossed cards can be scanned at horizontal feeding only)
			Feeding Capacity	
			60 sheets	

Type		Desktop sheetfed scanner	Interface		Hi-speed USB 2.0
Scanning element		Contact image sensor	Bundled software		CaptureOnTouch, CapturePerfect, eCopy PDF Pro Office, VRS
Light source		LED (red, green and blue)	Power supply		AC 100-240 V
Feeding method		Automatic	Power consumption		Scanning: 27 W, Sleep Mode: 1.8 W, Power Turned OFF: 0.5 W
Document thickness	Plain paper	Straight path Weight: 27 – 209 g/m ² Thickness: 0.04 – 0.25 mm	Operating environment	Temperature	10 – 32.5°C
		U-turn path Weight: 27 – 255 g/m ² Thickness: 0.04 – 0.3 mm		Humidity	20 – 80% RH
	PostCard	Weight: 128 – 300 g/m ² Thickness: 0.15 – 0.4 mm	Dimensions (width × depth × height)		Feed tray removed and eject tray closed: 280 × 172 × 178 mm Feed tray attached and eject tray open: 280 × 606 × 366.4 mm
	Business card	Weight: 380 g/m ² or less Thickness: 0.15 mm	Weight		Approx. 3.2 kg
	Card (ISO/IEC compliant)	0.76 mm or less Thickness: Up to 1.4 mm for embossed cards	Options/consumables		Barcode Module, 2D code Module, Exchange Roller Kit
Scanning side		Simplex / Duplex			