

DR-M260



A4

Capture Perfect

Capture OnTouch

- Newly developed SOC "DR Processor" realizes high speed /quality image processing without depending on PC performance
- Supports a variety of documents, including postcards, plastic cards, long document, and passports
- ADF holds up to 80 sheets
- Fast scanning at 60 ppm / 120 ipm, both color and B&W, single-pass double-sided
- Batch scanning features include Full Auto Mode, Skip Blank Page and Auto Page Size Detection, and more
- Bundled software includes ISIS/TWAIN Driver, CaptureOnTouch, CapturePerfect, VRS
- "Driver setting tool" which realizes easy customization of driver and scanner functions is bundled



Scanning speed		Document size	
A4/LTR, Portrait, 200dpi:			
	Simplex	Duplex	
Black and white	60 ppm	120 ipm	
Grayscale	60 ppm	120 ipm	
Color	60 ppm	120 ipm	
<i>*Actual scanning speed may vary depending on your system configuration and PC</i>			
Plain paper	A4/LTR	Width: 51 – 216 mm, Length: 54 – 356 mm	
Long document	✓	Up to 5,588 mm (200dpi)	
Postcard	✓	Width: 89 – 108 mm, Length: 127 – 152 mm	
Business card	✓	Width: 50 – 55 mm, Length: 85 – 91 mm	
Card (ISO/IEC compliant)	✓	54 x 86 mm (Horizontal feeding only. Embossed cards can be scanned)	
Passport	✓	88 x 125 mm (ISO standard) When scanning, be sure to open the passport and insert it in the provided carrier sheet (for passports) beforehand.	
Feeding Capacity			
80 sheets			

Type	Desktop sheet-fed scanner		Scanning side	Simplex / Duplex
Scanning element	CIS		Interface	SuperSpeed USB3.1 Gen1/Hi-Speed USB2.0
Light source	LED (red, green and blue)		Bundled software	ISIS/TWAIN Driver, CaptureOnTouch, CapturePerfect, VRS
Feeding method	Automatic		Power supply	AC100 – 240 V
Document thickness	Plain paper	Page separation mode: Weight: 27 – 413 g/m ² Thickness: 0.04 – 0.49 mm	Power consumption	Scanning: 23 W, Sleep mode: 1.4 W, Power Turned OFF: less than 0.1 W
		Non Separation Mode: Weight: 27 – 413 g/m ² Thickness: 0.04 – 0.49 mm	Operating environment	10 – 35°C
	Business card	Weight: 380 g/m ² or less Thickness: 0.45 mm	Temperature Humidity	20 – 80% RH
	Card (ISO/IEC compliant)	1.4 mm or less	Dimensions (width x depth x height)	Feed tray and eject tray closed: 285 x 254 x 231 mm Feed tray and eject tray open : 285 x 652 x 367 mm
Passport	6 mm or less (including carrier sheet)		Weight	Approx. 3.4 kg
			Options/consumables	Flatbed Scanner Unit 102, Barcode Module, 2D code Module, Exchange Roller Kit (feed roller and retard roller), Carrier Sheet (Passport), Carrier Sheet (A4), NA10