

P-215II



- Plug-and-scan capability without installing scanner driver
- Compact and lightweight scanner for easy portability
- Tidy single USB 3.0 port powering
- Fast scanning of A4/LTR at 15 ppm / 30 ipm (B&W, grayscale) and 10 ppm / 20 ipm (color), single-pass double-sided
- Card scanning with switch back mechanism
- "CaptureOnTouch" and "CaptureOnTouch Lite" ready
- Windows & Mac compatibility



Scanning speed		Document size																	
USB 2.0 bus power, A4/LTR, Portrait, 200dpi: <table border="0"> <tr> <td></td> <td>Simplex</td> <td>Duplex</td> <td></td> </tr> <tr> <td>Black and white</td> <td>12 ppm</td> <td>14 ipm</td> <td></td> </tr> <tr> <td>Grayscale</td> <td>12 ppm</td> <td>14 ipm</td> <td></td> </tr> <tr> <td>Color</td> <td>10 ppm</td> <td>10 ipm</td> <td></td> </tr> </table>			Simplex	Duplex		Black and white	12 ppm	14 ipm		Grayscale	12 ppm	14 ipm		Color	10 ppm	10 ipm		Plain paper A4/LTR Width: 51 – 216 mm, Length: 70 – 356 mm Long document ✓ Up to 1,000 mm Postcard ✓ Width: 89 – 108 mm, Length: 127 – 152.4 mm Business card ✓ Width: 49 – 55 mm, Length: 85 – 91 mm Card (ISO/IEC compliant) ✓ Width: 86 mm, Length: 54 mm	
	Simplex	Duplex																	
Black and white	12 ppm	14 ipm																	
Grayscale	12 ppm	14 ipm																	
Color	10 ppm	10 ipm																	
USB 3.0 bus power¹⁾, A4/LTR, Portrait, 200dpi: <table border="0"> <tr> <td></td> <td>Simplex</td> <td>Duplex</td> <td></td> </tr> <tr> <td>Black and white</td> <td>15 ppm</td> <td>30 ipm</td> <td></td> </tr> <tr> <td>Grayscale</td> <td>15 ppm</td> <td>30 ipm</td> <td></td> </tr> <tr> <td>Color</td> <td>10 ppm</td> <td>20 ipm</td> <td></td> </tr> </table>			Simplex	Duplex		Black and white	15 ppm	30 ipm		Grayscale	15 ppm	30 ipm		Color	10 ppm	20 ipm		Feeding Capacity 20 sheets	
	Simplex	Duplex																	
Black and white	15 ppm	30 ipm																	
Grayscale	15 ppm	30 ipm																	
Color	10 ppm	20 ipm																	
<small>*Actual scanning speed may vary depending on your system configuration and PC</small>																			

Type	Desktop sheet-fed scanner		Power supply	With USB 2.0 bus power: 0.5A (communication cable only) 1.0A (in combination with the power supply USB cable)
Scanning element	CIS			
Light source	LED (red, green and blue)		Power consumption	With USB 3.0 bus power: 0.9A With optional AC adapter: DC6V, 0.8A USB cable only: 2.5 W (USB 2.0) / 4.5 W (USB 3.0) USB cable and power supply cable: 5.0 W (USB 2.0) / 7.0 W (USB 3.0) Sleep mode: 1.5 W Power Turned OFF: 0.1 W
Feeding method	Automatic / card slot			
Document thickness	Plain paper	Weight: 52 – 128 g/m ² Thickness: 0.06 – 0.15 mm		
	Postcard	Weight: 128 – 225 g/m ² Thickness: 0.15 – 0.4 mm		
	Business card	Weight: 128 – 255 g/m ² Thickness: 0.15 – 0.3 mm		
	Card (ISO/IEC compliant)	Weight: 0.76 mm or less Thickness: Up to 1.4 mm for embossed cards		
Scanning side	Simplex / Duplex		Operating environment	Temperature 10 – 32.5°C
Interface	Hi-speed USB 2.0 (USB 3.0 bus power supported)		Humidity	25 – 80% RH
Bundled software	Windows:	ISIS/TWAIN driver, CaptureOnTouch, CaptureOnTouch Lite (built-in)	Dimensions (width x depth x height)	Feed tray closed: 285 x 95 x 40 mm Feed tray open: 285 x 257 x 174 mm
	Mac:	TWAIN driver, CaptureOnTouch, CaptureOnTouch Lite (built-in)	Weight	Approx. 1.0 kg
			Options/consumables	AC Adapter, Carrying Case, USB Cable, Separation Pad, Feed Roller