

ScanFront 400



A4

- The ScanFront 400 is a network scanner that allows scanning without a computer connection
- The large 10.1-inch touch panel provides easy viewability
- Scanning speeds of up to 45ppm/90ipm and the paper tray's 60-sheet loading capacity allow scanning of up to 6,000 sheets per day
- Scan directly to PC folders, E-mail addresses, FTP, USB memory, printers, and faxes
- Manage up to 1,000 scanner at the same time via the supplied Administration Tool for SF400 software
- The scanner is equipped with a web application server and web browser, allowing access and operation of the web application without the use of other devices
- Stable scanning is achieved via the scanner's reliable feeding and transport mechanisms



Scanning speed			Document size	
A4/LTR, Portrait, 200dpi (On standard mode):			Plain paper	A4/LTR Width: 50 – 216 mm, Length: 54 – 356 mm
	Simplex	Duplex	Long document	✓ Up to 3,048 mm in 200 dpi
Black and white	45 ppm	90 ipm	Postcard	—
Grayscale	45 ppm	90 ipm	Business card	✓ 50 × 85 mm
Color	45 ppm	90 ipm	Card (ISO/IEC compliant)	✓ 54 × 86 mm
*Actual scanning speed may vary depending on your system configuration and PC			Passport	✓ 88 × 125 mm (ISO standard) When scanning, be sure to open the passport and insert it in the provided carrier sheet (for passports) beforehand.
			Feeding Capacity	
			60 sheets (for A4/LTR) 40 sheets for document more than A4/LTR.	

Type	Pass-through desktop scanner with network compatibility		Scanning side	Simplex / Duplex	
Scanning element	CIS		Interface	Hi-Speed USB 2.0 (Type A x 3), LAN 10Base-T/100Base-TX/1000Base-T connector	
Light source	LED (red, green and blue)		Bundled software	ScanFront Administration Tool	
Feeding method	Automatic		Power supply	AC 100-240 V	
Document thickness	Plain paper	Page Separation mode: Weight: 27 to 209 g/m ² Thickness: 0.04 – 0.25 mm	Power consumption		Scanning: 36 W, Sleep mode: 2.0 W, Power Turned OFF: 0.2 W
		Non Separation mode: Weight: 27 to 255 g/m ² Thickness: 0.04 – 0.30 mm	Operating environment	Temperature	10 – 32.5°C
	Business card	380 g/m ² or less		Humidity	20 – 80% RH
	Card (ISO/IEC compliant)	1.4 mm or less	Dimensions (width × depth × height)	Feed tray and eject tray closed: 305 × 282 × 230 mm Feed tray and eject tray open: 305 × 629 × 366 mm	
	Passport	6 mm or less (including carrier sheet)	Weight	Approx. 4.5 kg	
			Options/consumables	Exchange Roller Kit, Flatbed Scanner Unit 102, Carrier Sheet (Passport), Carrier Sheet (A4)	