

## DUAL-CORE FANLESS TOUCH TERMINAL



# EC-1530

## SPECIFICATIONS



<b>CPU</b>	D525 dual core 1.8G; Intel Processor
<b>Memory</b>	DDRIII 1066/1333*1 2GB(up to 4GB)
<b>Storage</b>	SATA2.5 inch hard driver 160G; or 32GB SSD
<b>Chipset</b>	Intel D525+ICH8 Chipset
<b>Operation System</b>	Windows XP Professional, Windows XP Embedded, WEPOS, Linux
<b>Optional Peripherals</b>	ISO Track 1/2/3 Magnetic Stripe Reader; Customer pole Display : VFD; LED8; Wifi
<b>I/O Interface</b>	5* COM ports; 1*DB-VGA(15Pin D-sub), 1*DB25 Parallel port; 1* RJ-45 LAN port (1*Line-out, 1' MIC-in); 4* USB 2.0 1* Audio out; 2*Internal Speaker(option); 1* PS2 mouse ;1* PS2 key board.
<b>Panel</b>	
<b>viewing area</b>	15 inches
<b>Resolution</b>	1024*768 (max)
<b>Touch panel</b>	5-wire resistive
<b>Luminance</b>	250 cd/m
<b>Video Input</b>	
<b>VGA Signal</b>	LVDS
<b>Power Adaptor</b>	
<b>Input</b>	110-240V/50-60HZ AC
<b>Output</b>	DC 12V/5A
<b>Power Environment</b>	
<b>Management</b>	VESA DPMS
<b>Consumption</b>	35W
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Rotation</b>	
<b>Vertical</b>	130°
<b>Horizon</b>	140°
<b>Mounting</b>	
<b>Standard</b>	VESA Compliant (100mm x 100mm)
<b>Compliance</b>	FCC Class A / CE Mark / LVD / CCC
<b>Packing Information</b>	
<b>Dimension</b>	450*245*400mm
<b>Weight</b>	NW: 7KG    GW:9KG