

DUAL-CORE FANLESS TOUCH TERMINAL



Waterproof
Power by ELO

EC-1553 Specifications

CPU Type	Intel ® Celeron 1037U 1.80GHz (2MB Cache), Fanless
LCD	15" Active TFT color LCD, resolution 1024x768
Touch	5-wire Resistive Touch (PS2 Interface)
Memory	DDR3 SO-DIMM 2GB (2 x sockets support up to 4 GB)
LAN	10/100/1000 Mbps Gigabit Ethernet
Storage	Internal 2.5" SATA HDD x 1
I/O Interface	3* COM ports (COM1~2 powered with DC+0/5/12V via BIOS selection; COM3 without power) 1 * DB-15 VGA port 1 * RJ11 port supports 2 cash drawer (DC+24v) 1 * RJ-45 LAN port with activity and link LEDs 1 * PS/2 KB 1 * DC+12V out 6 * USB 2.0 1 * DC + 12V in (power adaptor)
Expansion Options	1 * Mini PCI-e
Optional Peripherals	3 Tracks Magnetic Reader Customer Display Module (2 x 20 VFD)
Operating System	Windows 7, Windows XP, XPe, Linux, (ubuntu , fedora), WEPOS, POSReady.
Power Supply	AC100~240V/DC+12V, 90 watts power adaptor
Dimensions	Physical:360 mm (W) x 233 mm (D) x 323 mm (H)
Operating Temp	0° C~+ 40° C
Storage temperature	-20° C~+ 60° C
Humidity	15%~80%
Certification	CE, FCC, CCC, VCCI, BSMI, Class A, KC

*specification subject to change without prior notice