

High Speed Label Printer



EC-3150 Features

- *3 inch print width
- *6 inch/sec ultra high printing
- *Support 2D barcode printing
- *Thermal continuous and sticker paper supported
- *Label paper auto positioned
- *Module design for different application
- *Support print media in 16 mm to 82mm range, easy operation design
- *Paper auto checkout and temperature auto controlled function
- *Simplified Chinese, Traditional Chinese and Korean character supported
- *Label paper peel-off and tear-off modes optional
- *Compatible with various label software
- *BMP, PCX, BAS files download and storage supported

Specifications

Print method	Direct thermal line
Print width	3inch
Resolution	203dpi
Print speed	3~6inch/s
Interface	Serial+USB+Ethernet / Parallel+USB
Media	Diameter: 25~85mm; Width: 16~82mm
Print head	Temperature sensor: thermal sensitive resistance; Position sensor: microswitch
Paper presence	Photoelectricity sensor
Enlargement	1to 10 times enlargement in both directions. 0°, 90°, 270°, 360° rotation
Barcode type	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2 EAN8+5/CODABAR/POSTNET/UPC-A/UPC+2/UPC+5/UPC-E/UPCE+2/UPC-E+5 CPOST/MSI/MSIC/PLESSEY/ITF14/EAN14/QRCODE(GP-3150TI)
Character size	FONT 0 to FONT 8 Simplified/Traditional Chinese/ Korean
Fonts	GB2312
Data	2M bytes
NV Flash	2M bytes
Cashdrawer out	DC 24V/1A
Power supply	DC 24V/2A
Power adaptor	Input: AC 110V/220V, 50~60Hz Output:DC 24V/2A
Weight	1.65KG
Dimension	230 x 156 x 147mm (L x W x H)
Work environment	Temperature: 0~45°C, Humidity: 10~80%
Storage environment	Temperature: -10~60°C, Humidity: 10~90%
Mechanism	150 Km