

Touch Screen Terminal



EC-1519

Features

- Power with EETI resistive touch screen
- Grade A industrial grade LED monitor
- Wall mount VESA mounting
- Various interfaces combination
- Fanless Al metal construction
- Optional second display and VFD & MSR
- Optional Elo touch solution
- HD / SSD available



Specifications

CPU
Memory
Storage
LAN
Operation System
Optional Peripherals

I/O Interface

Viewing Area
Resolution
Active Display Area (mm)
Display Color
Response Time
Contrast Ratio
Viewing Angle
Touch Panel
Luminance
Video Input (VGA Signal)
Input
Output
Management
Consumption
Storage Temperature
Operating Temperature
Operating Humidity
Rotation
Mounting (Standard)
Optional (Glass)

J1900 dual core 1.8G
DDRIII 1066/1333*1 2GB(up to 4GB)
32GB SSD / Optional 64GB / 128GB SSD
10/100/1000 Mbps gigabit Ethernet
Windows 7, Windows XP, XPe, Linux (Ubuntu, Fedora), WEPOS, POS eady
3 tracks magnetic reader
Customer display module (2*20 VFD)
10.4" LCD 2nd display module
5* COM ports;1*DB-VGA(15Pin D-sub)
1*DB25 Parallel port
1* RJ-45 LAN port (1*Line-out, 1' MIC-in);
4* USB 2.0
1* Audio out;
2*Internal Speaker(option)
1* PS2 mouse
1* PS2 key board.
15inches
800 x 600 or 1024 x 768 (max)
304.128 (W) x 228.96 (H)
16,777,216 colors
8 MS
600 : 1
(Up/ Down/ Left/ R 70° / 60° / 75° / 75°
5-wire resistive
250 cd/m
LVDS
110-240V/ AC 50-60HZ
DC 12V/5A
VESA DPMS
35W(max)
-20°C -- 60°C
0°C -- 40°C
10 % -- 85 %
130°(Vertical); 140°(Horizon)
VESA Compliant (100 mm x 100 mm)
Strengthen Glass (for none-touch version)

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.ecline.com.mx | ventas@ecline.com.mx

Asia, Pacifico y Europa: Unit A, 2/F, Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | email: sales@ecline.com.hk | support@ecline.com.hk