DTK-1651





DTK-1651

The DTK-1651 is the premium pen display for eDocuments which allows documents to be viewed, editied and signed in portrait mode without shrinking or scrolling or landscape mode. Slim. Innovative. Functional.

Best-in-class for comfort and security.

The DTK-1651 combines a 15.6" full HD resolution LCD display with state-of-the-art encryption. Its slim, sleek design leaves only a small footprint. With only one cable, the DTK-1651 eliminates cable clutter. The innovative pen holder and pen compartment create a convenient use.

- View and sign full-sized documents in A4 or Letter-size
- Convertible to portrait and landscape modes, flat on desk or 15° build-in stand
- 3-in-1 cable for power, HDMI and USB

Use case scenarios for eDocuments

Wacom's DTK-1651 is the premium product for banking, finance or insurance, education, healthcare, hospitality, telecoms or other POS retail solution. The DTK-1651 is the top-class product for all situations where the full document needs to be displayed for signing. The DTK-1651 can be easily integrated into existing infrastructure.

Accessories/spare parts are available separately, like stand with VESA adapter, pen, 3-in-1 cable, VGA-HDMI adapter, HDMI-VGA adapter, pen nib set, pen tether, AC adapter.



DTK-1651



General Specifications	
Dimensions (W x H x D, excluding stand)	420 x 286 x 17mm
Weight (including stand)	2.0 kg
Main body color	Black
Stand inclination	15°
Stand inclination	Integrated (landscape 15°/portrait 15°)
Power consumption	12 VDC, 3A (max)
Supported operating systems	Windows 10/8.1/8/7 (32-bit, 64-bit) Mac OSX 10.9 and later
LCD Display	
Display	IPS
Cover plate surface	Anti-glare etched glass
Screen diagonal	15.6" (344.16 x 193.59 mm)
Aspect ratio	16:9
Resolution	Full HD, 1920 x 1080 pixels
Viewing angles (horizontal/vertical)	170 °/ 170°
Luminance (brightness)	200 cd/ m ² (typical)
Contrast ratio	800:1 (typical)
Response time	30 ms (typical)
Backlight lifetime	25,000 hours
Tablet and pen	
Technology	Electromagnetic Resonance (EMR)
Active area	346.16 x 195.59 mm
Resolution	2,540 lpi
Coordinate accuracy	±0.5mm (center)
Report rate	197 points per second
Pressure levels	1,024
Miscellaneous	
Reading height	5 mm or more (center)
Pen storage	Integrated pen compartment, pen holder
Graphics card	N/A
Wall mount	VESA 75 mm
Software	Compatible with signature / E-signing software and Wacom sign pro PDF
Package content	Interactive pen display with integrated stand, cordless and battery-free pen, 3-in-1 cable (1.8 m/ 5.91 ft), installation CD (Wacom driver, product information), quick start guide,
	pen tether, (nylon fiber, 50 cm / 19.7 inch), 5 extra nibs, nib removal tool, power supply,
	power cable
Operating temperature, relative humidity	5 to 40 degrees C, Humidity: 30% to 80% RH (non-condensing)
Storage temperature,	-10 to 60 degree C, Humidity: 20% to 90% RH (non-condensing)
relative humidity	(Maximum storage humidity is 38% at a temperature of 60 degree C,
	and maximum strage temperature is 42 degree C at a humidity of 90%.)
Warranty	1 year

Wacom Singapore Pte Ltd. +65 6337 9394 solutions@wacom.com.sg